



Specification

Model No.:	RS-FT36W316X(88104) / RS-FT40W316X(88104)
Front cover & Housing:	Stainless steel 316L
Dimensions:	D180*H36mm (Nozzle hole size: 47mm)
Tempered Glass:	5mm thickness
LED chip:	CREE
LED Q'ty:	12pcs 3W LED / 10pcs 4in1 LED
Cable gland:	Stainless steel 316L PG13.5
Driver:	Constant current driver
Lens:	Clear, Bead, Frosted
Beam Angle Options:	10° 20° 30° 45° 60° 90°
Power Cable:	AWG 5/18 or AWG 3/18 SOW rubber cable
Protection Class:	IP68
Environment:	Dry / Submerged
Mounting Hardware:	Surface Mounted System / Nozzle fixed
Net Weight:	3.0kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88104.123.01	2700-3000K	12*3	V+/V-	AC/DC24	1500	36	1680
88104.123.02	4000-4500K	12*3	V+/V-	AC/DC24	1500	36	1776
88104.123.03	5000-5500K	12*3	V+/V-	AC/DC24	1500	36	1860
88104.123.04	6000-6500K	12*3	V+/V-	AC/DC24	1500	36	1860
88104.123.05	Red	12*3	V+/V-	AC/DC24	1000	24	420
88104.123.06	Green	12*3	V+/V-	AC/DC24	1500	36	1080
88104.123.07	Blue	12*3	V+/V-	AC/DC24	1500	36	480
88104.123.08	Yellow	12*3	V+/V-	AC/DC24	1500	36	1140
88104.123.09	RGB-DMX512 (3 channel)	12*3	V+ /V- /D+ /D- /GND	AC/DC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88104.123.10	Auto changing color	12*3	V+/V-	AC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88104.123.12	RGBV+ (build-in CC driver)	12*3	R/G/B/V+	DC24	R: 333 B: 500 G: 500	R: 8 B: 12 G: 12	R: 140 B: 160 G: 360
88104.104.13	RGBW-DMX512 (4 channel)	10*4in1	V+ /V- /D+ /D- /GND	AC/DC24	R: 416 B: 416 G: 416 W: 416	R: 10 B: 10 G: 10 W: 10	R: 250 B: 300 G: 600 W: 900

