




### Product Size



### Specification

<b>Model No.:</b>	RS-RP27W316X-FT(88129) / RS-RP24W316X-FT(88129)
<b>Front cover &amp; Housing:</b>	Stainless steel 316L
<b>Dimensions:</b>	D200*H33mm [Nozzle hole size: 47mm; G1 ½]
<b>Tempered Glass:</b>	10mm thickness
<b>LED chip:</b>	CREE
<b>LED Q'ty:</b>	9pcs 3W LED / 6pcs 4in1 LED
<b>Cable gland:</b>	Stainless steel 316L PG13.5
<b>Driver:</b>	Constant current driver
<b>Lens:</b>	Clear, Bead, Frosted
<b>Beam Angle Options:</b>	10° 30° 45° 70°
<b>Power Cable:</b>	AWG 5/18 or AWG 3/18 SOW rubber cable
<b>Protection Class:</b>	IP68
<b>Environment:</b>	Dry / Submerged
<b>Mounting Hardware:</b>	Surface Mounted System / Nozzle fixed
<b>Net Weight:</b>	3.0kgs with 1.5m cable
<b>Lifetime:</b>	>50000H

### Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88129.093.01	2700-3000K	9*3	V+/V-	AC/DC12-24	2250 / 1125	27	1260
88129.093.02	4000-4500K	9*3	V+/V-	AC/DC12-24	2250 / 1125	27	1332
88129.093.03	5000-5500K	9*3	V+/V-	AC/DC12-24	2250 / 1125	27	1395
88129.093.04	6000-6500K	9*3	V+/V-	AC/DC12-24	2250 / 1125	27	1395
88129.093.05	Red	9*3	V+/V-	AC/DC12-24	1500 / 750	18	315
88129.093.06	Green	9*3	V+/V-	AC/DC12-24	2250 / 1125	27	810
88129.093.07	Blue	9*3	V+/V-	AC/DC12-24	2250 / 1125	27	360
88129.093.08	Yellow	9*3	V+/V-	AC/DC12-24	2250 / 1125	27	855
88129.093.09	RGB-DMX512 (3 channel)	9*3	V+ /V-/D+/D-/GND	AC/DC12-24	R: 500 / 250 B: 750 / 375	R: 6 G: 9 B: 9	R: 105 G: 270 B: 120
88129.093.10	Auto changing color	9*3	V+/V-	AC12-24	R: 500 / 250 B: 750 / 375	R: 6 G: 9 B: 9	R: 105 G: 270 B: 120
88129.093.12	RGBV+ (build-in CC driver)	9*3	R/G/B/V+	DC12-24	R: 500 / 250 B: 750 / 375	R: 6 G: 9 B: 9	R: 105 G: 270 B: 120
88129.064.14	RGBW-DMX512 (4 channel)	6*4in1	V+ /V-/D+/D-/GND	DC24	R: 250 G: 250 B: 250 W: 250	R: 6 G: 6 B: 6 W: 6	R: 150 G: 360 B: 180 W: 540

