


NEW



Product Size



Specification

Model No.:	RS-UW36W316X-L-SA(88454)
Front cover & Housing:	Stainless steel 316L
Dimensions:	L177*W96*H60mm(Max.)
Tempered Glass:	8mm thickness
LED chip:	Cree
LED Q'ty:	9pcs 3W LED / 12pcs 3W LED
Cable gland:	Stainless steel 316L PG13.5
Driver:	Constant current driver
Lens:	Clear, Bead
Beam Angle Options:	10° 30° 60°
Power Cable:	AWG 5/18 or AWG 3/18 SOW rubber cable
Protection Class:	IP68
Environment:	Dry / Submerged
Mounting Hardware:	Surface Mounted System
Net Weight:	1.8kgs with 1.5m cable
Lifetime:	>50000H

Order information

Item code	Color	Light source(w)	Line Way	Input Voltage (v)	Operating current (mA)	Consumption (w)	Luminous (lm)
88454.093.01	2700-3000K	9*3	V+/V-	AC/DC24	1500	27	1260
88454.093.02	4000-4500K	9*3	V+/V-	AC/DC24	1500	27	1332
88454.093.03	5000-5500K	9*3	V+/V-	AC/DC24	1500	27	1395
88454.093.04	6000-6500K	9*3	V+/V-	AC/DC24	1500	27	1395
88454.093.05	Red	9*3	V+/V-	AC/DC24	1500	18	315
88454.093.06	Green	9*3	V+/V-	AC/DC24	1500	27	810
88454.093.07	Blue	9*3	V+/V-	AC/DC24	1500	27	360
88454.093.08	Yellow	9*3	V+/V-	AC/DC24	1500	27	855
88454.093.09	RGB-DMX512 (3 channel)	9*3	V+ /V-/D+/D-/GND	DC24	R: 250 B: 375	R: 6 B: 9	R: 105 B: 120
88454.123.12	RGBW-DMX512 (4 channel)	12*3	V+ /V-/D+/D-/GND	DC24	R: 500 B: 500 G: 500 W: 500	R: 12 B: 12 G: 12 W: 12	R: 300 B: 360 G: 720 W: 1080

